


Appendix 2 - Web Services Definition

A2.1 Web Services Overview


The ontological elements of the Content Model for Reuse include a Web Services Definition Language (WSDL) that defines the systems interfaces at each layer of the model and an XML schema describing the document exchange formats. The WSDL definition provides the framework for application interfaces to the systems model. Other interfaces were designed in the course of the project. They were oriented to providing a framework for authoring and publish access to the Inter-Publish prototype as described in the architecture diagram below.



A2.2 Web Services Definition

The Web Services interface is itself a four layer model. The layered approach of the web services definition is directed primarily to achieve transport independence (the services layer) and well documented functional separation of the services provided. The bindings are the principal point of interface through to operations with specific document exchange specifications. In the definition below, the documents exchanged using the web services functions are defined by the CMR xml schema shown in Section A2.3 below. The current Web Services Definition Language (WSDL) specification may be found at <http://www.interpublish.com.au/interpublish.wsdl>.

The following diagram is an overview of the Inter-Publish web services interface, followed by a detailed description of each of the bindings and operations.



services	bindings	porttypes	messages
interpublish	ipwebserviceSoap Binding	ipwebserviceSoapPort	ipwebservice.cmr_Deleteddocuments ipwebservice.cmr_DeleteddocumentsResponse ipwebservice.cmr_Editdocuments ipwebservice.cmr_EditdocumentsResponse ipwebservice.cmr_Getcollectioncriteria ipwebservice.cmr_GetcollectioncriteriaResponse ipwebservice.cmr_Getcollectiondocuments ipwebservice.cmr_GetcollectiondocumentsResponse ipwebservice.cmr_Getdocumentdefinition ipwebservice.cmr_GetdocumentdefinitionResponse ipwebservice.cmr_Getdocumentpreview ipwebservice.cmr_GetdocumentpreviewResponse ipwebservice.cmr_Getdocuments ipwebservice.cmr_GetdocumentsResponse ipwebservice.cmr_Getecu ipwebservice.cmr_GetecuResponse ipwebservice.cmr_Getelementdefinition ipwebservice.cmr_GetelementdefinitionResponse ipwebservice.cmr_Getsyndication ipwebservice.cmr_GetsyndicationResponse ipwebservice.cmr_Listcollections ipwebservice.cmr_ListcollectionsResponse ipwebservice.cmr_Listdocuments ipwebservice.cmr_ListdocumentsResponse ipwebservice.cmr_Login ipwebservice.cmr_LoginResponse ipwebservice.cmr_Releaseddocuments ipwebservice.cmr_ReleaseddocumentsResponse ipwebservice.cmr_Releaseecu ipwebservice.cmr_ReleaseecuResponse ipwebservice.cmr_Saveddocuments ipwebservice.cmr_SaveddocumentsResponse ipwebservice.cmr_Updatecollection ipwebservice.cmr_UpdatecollectionResponse ipwebservice.cmr_Updateddocumentdefinition ipwebservice.cmr_UpdateddocumentdefinitionResponse ipwebservice.cmr_Updateecu ipwebservice.cmr_UpdateecuResponse ipwebservice.cmr_Updateelementdefinition ipwebservice.cmr_UpdateelementdefinitionResponse

service **interpublish**

ports	IpwebserviceSoapPort
binding	wsdltns:ipwebserviceSoapBinding

binding ipwebserviceSoapBinding


type	wsdl:ns:ipwebserviceSoapPort
operations	cmr_Updateecu input <code><soap:body parts="cmr_Eculist" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> output <code><soap:body parts="Result" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> cmr_Getsyndication input <code><soap:body parts="cmr_Syndicationrequest" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> output <code><soap:body parts="Result" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> cmr_Updatecollection input <code><soap:body parts="cmr_Collectionlist" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> output <code><soap:body parts="Result" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> cmr_Updatedocumentdefinition input <code><soap:body parts="cmr_Documenttypelist" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> output <code><soap:body parts="Result" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> cmr_Updateelementdefinition input <code><soap:body parts="cmr_Elementlist" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> output <code><soap:body parts="Result" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> cmr_Getcollectioncriteria input <code><soap:body parts="cmr_Selectionrule" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> output <code><soap:body parts="Result" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> cmr_Getdocumentdefinition input <code><soap:body parts="cmr_Selectionrule" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> output <code><soap:body parts="Result" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> cmr_Getelementdefinition input <code><soap:body parts="cmr_Selectionrule" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> output <code><soap:body parts="Result" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> cmr_Getecu input <code><soap:body parts="cmr_Selectionrule" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> output <code><soap:body parts="Result" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> cmr_Login input <code><soap:body parts="cmr_Auth" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> output <code><soap:body parts="Result" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code> cmr_Getdocuments input <code><soap:body parts="cmr_Urmlist" use="encoded" encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://www2.prosient.com.au/interpublish/message/"></code>

[illegible]

A2.3 CMR Schema

This section presents each element in the realisation of the CMR as an XML schema used in the web services interface for each layer of the model..

The XML schema provides the document ontology required at the four layers of the CMR. At each layer content documents are required to provide the content interchange definition. In practical implementation an 'auth' element is required with each transaction. The ontology for these content documents is described through an XML schema in this section, and can be reviewed at <http://www.it.usyd.edu.au/~ejb/cmr.xsd>.



element **auth**

	auth cmr_Status 1..∞ Basic authentication for the CMR. 'Clientid', 'authorid' and 'password' are provided with the first request. A 'sessionid' token will be returned and may be supplied for all transactions thereafter. This element also defines the namespace element 'clientid' which provides the context for all content identification and document transactions. A status report on all update and request actions. Return values are 'OK' or 'Failed' with a failure explanation in element 'description'.															
children	cmr_Status															
used by	element cmr															
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>clientid</td><td>xs:string</td><td>required</td></tr><tr><td>authorid</td><td>xs:string</td><td></td></tr><tr><td>password</td><td>xs:string</td><td></td></tr><tr><td>sessionid</td><td>xs:string</td><td></td></tr></table>	Name	Type	Use	clientid	xs:string	required	authorid	xs:string		password	xs:string		sessionid	xs:string	
Name	Type	Use														
clientid	xs:string	required														
authorid	xs:string															
password	xs:string															
sessionid	xs:string															
notes	Basic authentication for the CMR. 'Clientid', 'authorid' and 'password' are provided with the first request. A 'sessionid' token will be returned and may be supplied for all transactions thereafter. This element also defines the namespace element 'clientid' which provides the context for all content identification and document transactions.															
xml	<pre><xs:element name="auth"> <xs:notes> <xs:documentation>Basic authentication for the CMR. 'Clientid', 'authorid' and 'password' are provided with the first request. A 'sessionid' token will be returned and may be supplied for all transactions thereafter. This element also defines the namespace element 'clientid' which provides the context for all content identification and document transactions.</xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Status" maxOccurs="unbounded"/> </xs:sequence> <xs:attribute name="clientid" type="xs:string" use="required"/> <xs:attribute name="authorid" type="xs:string"/> <xs:attribute name="password" type="xs:string"/> <xs:attribute name="sessionid" type="xs:string"/> </xs:complexType> </xs:element></pre>															

element **cmr_Collection**

	 cmr_Collection The collection defines a set of selection criteria for a persistent search definition. A collection may include a reference to another collection to provide complex search structures. cmr_Collectioncriteria The collection criteria define a specific selection rule or a reference to another collection. Criteria Values may contain a multi-list single quoted and separated by commas or semicolons.		
children	cmr_Collectioncriteria		
used by	element	cmr_Collectionlist	
attributes	Name	Type	Use
	action	xs:NMTOKEN	required
	collectionid	xs:string	required
	sectionname	xs:string	required
	status	xs:string	
	instructions	xs:string	
	shortdescription	xs:string	
notes	The collection defines a set of selection criteria for a persistent search definition. A collection may include a reference to another collection to provide complex search structures.		
xml	<pre> <xs:element name="cmr_Collection"> <xs:notes> <xs:documentation>The collection defines a set of selection criteria for a persistent search definition. A collection may include a reference to another collection to provide complex search structures.</xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Collectioncriteria"/> </xs:sequence> <xs:attribute name="action" use="required"> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="update"/> <xs:enumeration value="generate"/> <xs:enumeration value="publish"/> <xs:enumeration value="delete"/> <xs:enumeration value="get"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="collectionid" type="xs:string" use="required"/> <xs:attribute name="sectionname" type="xs:string" use="required"/> <xs:attribute name="status" type="xs:string"/> <xs:attribute name="instructions" type="xs:string"/> <xs:attribute name="shortdescription" type="xs:string"/> </xs:complexType> </xs:element> </pre>		

element **cmr_Collectioncriteria**

	cmr_Collectioncriteria The collection criteria define a specific selection rule or a reference to another collection. Criteria Values may contain a multi-list single quoted and separated by commas or semicolons.												
used by	element cmr_Collection												
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>criteriaelement</td><td>xs:string</td><td>required</td></tr><tr><td>criteriacomparison</td><td>xs:string</td><td>required</td></tr><tr><td>criteriavalues</td><td>xs:string</td><td>required</td></tr></table>	Name	Type	Use	criteriaelement	xs:string	required	criteriacomparison	xs:string	required	criteriavalues	xs:string	required
Name	Type	Use											
criteriaelement	xs:string	required											
criteriacomparison	xs:string	required											
criteriavalues	xs:string	required											
notes	The collection criteria define a specific selection rule or a reference to another collection. Criteria Values may contain a multi-list single quoted and separated by commas or semicolons.												
xml	<pre><xs:element name="cmr_Collectioncriteria"> <xs:notes > <xs:documentation>The collection criteria define a specific selection rule or a reference to another collection. Criteria Values may contain a multi-list single quoted and separated by commas or semicolons.</xs:documentation> </xs:notes > <xs:complexType> <xs:attribute name="criteriaelement" type="xs:string" use="required"/> <xs:attribute name="criteriacomparison" type="xs:string" use="required"/> <xs:attribute name="criteriavalues" type="xs:string" use="required"/> </xs:complexType> </xs:element></pre>												

element **cmr_Collectionlist**

	cmr_Collectionlist A collection of persistent search definitions. cmr_Collection The collection defines a set of selection criteria for a persistent search definition. A collection may include a reference to another collection to provide complex search structures. cmr_Documentlist 0..∞ A collection of CMR documents or document elements or document references. cmr_Status 1..∞ A status report on all update and request actions. Return values are 'OK' or 'Failed' with a failure explanation in element 'description'.
children	cmr_Collection cmr_Documentlist cmr_Status
used by	element cmr
notes	A collection of persistent search definitions.
xml	<pre><xs:element name="cmr_Collectionlist"> <xs:notes></pre>

	<pre> <xs:documentation>A collection of persistent search definitions.</xs:documentation> <xs:notes > <xs:complexType> <xs:sequence> <xs:element ref="cmr_Collection"/> <xs:element ref="cmr_Documentlist" minOccurs="0" maxOccurs="unbounded"/> <xs:element ref="cmr_Status" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **cmr_Data_event**

	 cmr_Data_event The definition for a data-driven workflow event.																					
type	extension of xs:string																					
used by	element cmr_Workflow																					
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>elementname</td><td>xs:string</td><td>required</td></tr><tr><td>elementvalues</td><td>xs:string</td><td>required</td></tr><tr><td>action</td><td>xs:NMTOKEN</td><td>required</td></tr><tr><td>alertgroup</td><td>xs:string</td><td>required</td></tr><tr><td>nextdocumenttype</td><td>xs:string</td><td>required</td></tr><tr><td>nextstatus</td><td>xs:string</td><td></td></tr></table>	Name	Type	Use	elementname	xs:string	required	elementvalues	xs:string	required	action	xs:NMTOKEN	required	alertgroup	xs:string	required	nextdocumenttype	xs:string	required	nextstatus	xs:string	
Name	Type	Use																				
elementname	xs:string	required																				
elementvalues	xs:string	required																				
action	xs:NMTOKEN	required																				
alertgroup	xs:string	required																				
nextdocumenttype	xs:string	required																				
nextstatus	xs:string																					
notes	The definition for a data-driven workflow event.																					
xml	<pre><xs:element name="cmr_Data_event"> <xs:notes > <xs:documentation>The definition for a data-driven workflow event.</xs:documentation> </xs:notes > <xs:complexType> <xs:simpleContent> <xs:extension base="xs:string"> <xs:attribute name="elementname" type="xs:string" use="required"/> <xs:attribute name="elementvalues" type="xs:string" use="required"/> <xs:attribute name="action" use="required"/> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="publish"/> <xs:enumeration value="changedocumenttype"/> <xs:enumeration value="email"/> <xs:enumeration value="changedocumentstatus"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="alertgroup" type="xs:string" use="required"/> <xs:attribute name="nextdocumenttype" type="xs:string" use="required"/> <xs:attribute name="nextstatus" type="xs:string"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>																					


element **cmr_Document**

	<pre> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="create"/> <xs:enumeration value="update"/> <xs:enumeration value="delete"/> <xs:enumeration value="archive"/> <xs:enumeration value="publish"/> <xs:enumeration value="get"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="title" type="xs:string" use="required"/> <xs:attribute name="documenttype" type="xs:string" use="required"/> <xs:attribute name="sectionname" type="xs:string" use="required"/> <xs:attribute name="contenttype" type="xs:string" use="required"/> <xs:attribute name="externalid" type="xs:string"/> <xs:attribute name="documentstatus" use="required"> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="published"/> <xs:enumeration value="unpublished"/> <xs:enumeration value="deleted"/> <xs:enumeration value="archived"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="datelastedited" type="xs:string" use="required"/> </xs:complexType> </xs:element> </pre>
--	--

element **cmr_Documentelement**

	cmr_Documentelement The specific presentation instructions for an element of a form. <pre>graph LR cmr_Documentelement[cmr_Documentelement] --> seq[...] seq --> cmr_Element[cmr_Element]</pre> cmr_Element The definition for the encoding and presentation of an ECU fragment type.									
children	cmr_Element									
used by	element cmr_Documenttype									
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>formprefix</td><td>xs:string</td><td>required</td></tr><tr><td>formsuffix</td><td>xs:string</td><td>required</td></tr></table>	Name	Type	Use	formprefix	xs:string	required	formsuffix	xs:string	required
Name	Type	Use								
formprefix	xs:string	required								
formsuffix	xs:string	required								
notes	The specific presentation instructions for an element of a form.									
xml	<pre><xs:element name="cmr_Documentelement"> <xs:notes> <xs:documentation>The specific presentation instructions for an element of a form.</xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Element"/> </xs:sequence> <xs:attribute name="formprefix" type="xs:string" use="required"/> <xs:attribute name="formsuffix" type="xs:string" use="required"/> </xs:complexType> </xs:element></pre>									

element **cmr_Documentlist**

	 <pre> classDiagram class cmr_Documentlist { } class cmr_Document { } class cmr_Status { } cmr_Documentlist "1" -- "1..∞" cmr_Document cmr_Documentlist "1" -- "1..∞" cmr_Status </pre> cmr_Documentlist A collection of CMR documents or document elements or document references. cmr_Document A cmr document comprising a set of fragmented economic bought together under the umbrella of a document type structure. The attributes of 'title', 'documenttype', 'sectionname', 'contenttype', 'documentstatus' are mandatory for purposes of workflow management. Where the action is 'update' either a documentid or an 'externalid' may be supplied for matching - failure to match or absence of both will result in creation of a new document. cmr_Status A status report on all update and request actions. Return values are 'OK' or 'Failed' with a failure explanation in element 'description'.
children	cmr_Document cmr_Status
used by	elements cmr cmr_Collectionlist
notes	A collection of CMR documents or document elements or document references.
xml	<pre> <xs:element name="cmr_Documentlist"> <xs:notes> <xs:documentation>A collection of CMR documents or document elements or document references.</xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Document" maxOccurs="unbounded"/> <xs:element ref="cmr_Status" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **cmr_Documenttype**

	 cmr_Documenttype A form-based document definition, defining a collection of elements to be presented for form based capture of content. The sequence is significant in presentation of the data entry form. cmr_Documentelement The specific presentation instructions for an element of a form.
children	cmr_Documentelement

used by	element cmr_Documenttypelist		
attributes	Name	Type	Use
	documenttype	xs:string	required
	language	xs:string	required
notes	A form-based document definition, defining a collection of elements to be presented for form based capture of content. The sequence is significant in presentation of the data entry form.		
xml	<pre> <xs:element name="cmr_Documenttype"> <xs:notes > <xs:documentation>A form-based document definition, defining a collection of elements to be presented for form based capture of content. The sequence is significant in presentation of the data entry form.</xs:documentation> </xs:notes > <xs:complexType> <xs:sequence> <xs:element ref="cmr_Documentelement"/> </xs:sequence> <xs:attribute name="documenttype" type="xs:string" use="required"/> <xs:attribute name="language" type="xs:string" use="required"/> </xs:complexType> </xs:element> </pre>		


element **cmr_Documenttype_event**

	cmr_Documenttype_event A workflow event definition for the actions required when a document changes status.		
used by	element cmr_Workflow		
attributes	Name	Type	Use
	action	xs:NMTOKEN	required
	alertgroup	xs:string	
	nextdocumenttype	xs:string	
	nextstatus	xs:string	
notes	A workflow event definition for the actions required when a document changes status.		
xml	<pre> <xs:element name="cmr_Documenttype_event"> <xs:notes > <xs:documentation>A workflow event definition for the actions required when a document changes status.</xs:documentation> </xs:notes > <xs:complexType> <xs:attribute name="action" use="required"> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="publish"/> <xs:enumeration value="changedocumenttype"/> <xs:enumeration value="email"/> <xs:enumeration value="changedocumentstatus"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="alertgroup" type="xs:string"/> <xs:attribute name="nextdocumenttype" type="xs:string"/> <xs:attribute name="nextstatus" type="xs:string"/> </xs:complexType> </xs:element> </pre>		

element **cmr_Documenttypelist**

	<pre> <xs:attribute name="cmr_Fragmentationlevel" use="required"> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="completedocument"/> <xs:enumeration value="textpage"/> <xs:enumeration value="textparagraph"/> <xs:enumeration value="multimediasegment"/> </xs:restriction> </xs:simpleType> </xs:attribute> </xs:complexType> </xs:element> </pre>
--	--

element **cmr_Eculist**

	 A collection of Economic Content Units. 1..∞ An ECU - a semantically coherent fragment of content or multimedia.
children	cmr_Ecu
used by	elements cmr cmr_Document
notes	A collection of Economic Content Units.
xml	<pre> <xs:element name="cmr_Eculist"> <xs:notes> <xs:documentation>A collection of Economic Content Units.</xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Ecu" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **cmr_Element**

	cmr_Element The definition for the encoding and presentation of an ECU fragment type.																											
used by	element cmr_Documentelement																											
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>element</td><td>xs:string</td><td>required</td></tr><tr><td>elementtype</td><td>xs:NMTOKEN</td><td>required</td></tr><tr><td>elementusage</td><td>xs:NMTOKEN</td><td>required</td></tr><tr><td>description</td><td>xs:string</td><td>required</td></tr><tr><td>inputsize</td><td>xs:string</td><td>required</td></tr><tr><td>maxinput</td><td>xs:string</td><td>required</td></tr><tr><td>selectionvalues</td><td>xs:string</td><td>required</td></tr><tr><td>subelements</td><td>xs:string</td><td>required</td></tr></table>	Name	Type	Use	element	xs:string	required	elementtype	xs:NMTOKEN	required	elementusage	xs:NMTOKEN	required	description	xs:string	required	inputsize	xs:string	required	maxinput	xs:string	required	selectionvalues	xs:string	required	subelements	xs:string	required
Name	Type	Use																										
element	xs:string	required																										
elementtype	xs:NMTOKEN	required																										
elementusage	xs:NMTOKEN	required																										
description	xs:string	required																										
inputsize	xs:string	required																										
maxinput	xs:string	required																										
selectionvalues	xs:string	required																										
subelements	xs:string	required																										
notes	The definition for the encoding and presentation of an ECU fragment type.																											
xml	<pre><xs:element name="cmr_Element"> <xs:notes> <xs:documentation>The definition for the encoding and presentation of an ECU fragment type.</xs:documentation> </xs:notes></pre>																											

	<pre><xs:complexType> <xs:attribute name="element" type="xs:string" use="required"/> <xs:attribute name="elementtype" use="required"/> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="textline"/> <xs:enumeration value="textblob"/> <xs:enumeration value="multimediablob"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="elementusage" use="required"> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="date"/> <xs:enumeration value="input"/> <xs:enumeration value="xml"/> <xs:enumeration value="html"/> <xs:enumeration value="text"/> <xs:enumeration value="numeric"/> <xs:enumeration value="logical"/> <xs:enumeration value="checkboxlist"/> <xs:enumeration value="lookupdocumentcontents"/> <xs:enumeration value="selectionlist"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="description" type="xs:string" use="required"/> <xs:attribute name="inputsize" type="xs:string" use="required"/> <xs:attribute name="maxinput" type="xs:string" use="required"/> <xs:attribute name="selectionvalues" type="xs:string" use="required"/> <xs:attribute name="subelements" type="xs:string" use="required"/> </xs:complexType> </xs:element></pre>
--	--

element **cmr_Encodeddocument**

	cmr_Encodeddocument A single encoded and transformed document ready for final presentation.
type	xs:string
used by	element cmr_url
notes	A single encoded and transformed document ready for final presentation.
xml	<pre><xs:element name="cmr_Encodeddocument" type="xs:string"> <xs:notes> <xs:documentation>A single encoded and transformed document ready for final presentation.</xs:documentation> </xs:notes> </xs:element></pre>

element **cmr_Encodingvariant**

	<pre> <xs:element ref="cmr_Encodingvariant"/> </xs:sequence> <xs:attribute name="language" type="xs:string" use="required"/> <xs:attribute name="element" type="xs:string" use="required"/> </xs:complexType> </xs:element> </pre>
--	--

element **cmr_Metadata**

	cmr_Metadata Metadata content.															
used by	elements cmr_Ecu cmr_Encodingvariant															
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>contenttype</td><td>xs:string</td><td>required</td></tr><tr><td>transferencoding</td><td>xs:string</td><td>required</td></tr><tr><td>element</td><td>xs:string</td><td>required</td></tr><tr><td>fragmentationlevel</td><td>xs:NMTOKEN</td><td>required</td></tr></table>	Name	Type	Use	contenttype	xs:string	required	transferencoding	xs:string	required	element	xs:string	required	fragmentationlevel	xs:NMTOKEN	required
Name	Type	Use														
contenttype	xs:string	required														
transferencoding	xs:string	required														
element	xs:string	required														
fragmentationlevel	xs:NMTOKEN	required														
notes	Metadata content.															
xml	<pre><xs:element name="cmr_Metadata"> <xs:notes > <xs:documentation>Metadata content.</xs:documentation> </xs:notes > <xs:complexType> <xs:attribute name="contenttype" type="xs:string" use="required"/> <xs:attribute name="transferencoding" type="xs:string" use="required"/> <xs:attribute name="element" type="xs:string" use="required"/> <xs:attribute name="fragmentationlevel" use="required"/> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="completedocument"/> <xs:enumeration value="textpage"/> <xs:enumeration value="textparagraph"/> <xs:enumeration value="multimediasegment"/> </xs:restriction> </xs:simpleType> </xs:attribute> </xs:complexType> </xs:element></pre>															

element **cmr_profile**

	cmr_profile The profile id to be used to return a transformed specific set of syndication documents.									
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>profileid</td><td>xs:string</td><td>required</td></tr><tr><td>encoding</td><td>xs:string</td><td>required</td></tr></table>	Name	Type	Use	profileid	xs:string	required	encoding	xs:string	required
Name	Type	Use								
profileid	xs:string	required								
encoding	xs:string	required								
notes	The profile id to be used to return a transformed specific set of syndication documents.									
xml	<pre><xs:element name="cmr_profile"> <xs:notes> <xs:documentation>The profile id to be used to return a transformed specific set of syndication documents.</xs:documentation> </xs:notes> <xs:complexType> <xs:attribute name="profileid" type="xs:string" use="required"/> <xs:attribute name="encoding" type="xs:string" use="required"/> </xs:complexType> </xs:element></pre>									

	<code></xs:complexType></code> <code></xs:element></code>
--	--

element **cmr_Selectionelement**

	cmr_Selectionelement A transient selection request returning a set of documents for authoring. The attribute 'SelectionType' specifies the type of selection rule to be applied that can be further qualified by the attribute SelectionElement and SelectionValue. Where 'SelectionType' as a value of 'Element' then an Inter-Publish Element must be specified in the attribute 'SelectionElement' with a value or set of values in the attribute 'SelectionValue'. More complex selection rules can be defined through static collections.																		
used by	<table><tr><th>element</th><th>cmr_Selectionrule</th></tr></table>	element	cmr_Selectionrule																
element	cmr_Selectionrule																		
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>action</td><td>xs:NMTOKEN</td><td></td></tr><tr><td>selectiontype</td><td>xs:NMTOKEN</td><td>required</td></tr><tr><td>selectionelement</td><td>xs:string</td><td>required</td></tr><tr><td>selectioncomparison</td><td>xs:string</td><td>required</td></tr><tr><td>selectionvalue</td><td>xs:string</td><td>required</td></tr></table>	Name	Type	Use	action	xs:NMTOKEN		selectiontype	xs:NMTOKEN	required	selectionelement	xs:string	required	selectioncomparison	xs:string	required	selectionvalue	xs:string	required
Name	Type	Use																	
action	xs:NMTOKEN																		
selectiontype	xs:NMTOKEN	required																	
selectionelement	xs:string	required																	
selectioncomparison	xs:string	required																	
selectionvalue	xs:string	required																	
notes	A transient selection request returning a set of documents for authoring. The attribute 'SelectionType' specifies the type of selection rule to be applied that can be further qualified by the attribute SelectionElement and SelectionValue. Where 'SelectionType' as a value of 'Element' then an Inter-Publish Element must be specified in the attribute 'SelectionElement' with a value or set of values in the attribute 'SelectionValue'. More complex selection rules can be defined through static collections.																		
xml	<pre><xs:element name="cmr_Selectionelement"> <xs:notes> <xs:documentation>A transient selection request returning a set of documents for authoring. The attribute 'SelectionType' specifies the type of selection rule to be applied that can be further qualified by the attribute SelectionElement and SelectionValue. Where 'SelectionType' as a value of 'Element' then an Inter-Publish Element must be specified in the attribute 'SelectionElement' with a value or set of values in the attribute 'SelectionValue'. More complex selection rules can be defined through static collections.</xs:documentation> </xs:notes> <xs:complexType> <xs:attribute name="action"> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="lock"/> <xs:enumeration value="nolock"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="selectiontype" use="required"> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="element"/> <xs:enumeration value="documenttype"/> <xs:enumeration value="sectionname"/> <xs:enumeration value="elementdefinition"/> <xs:enumeration value="documenttypedefinition"/> <xs:enumeration value="element"/> </xs:restriction> </xs:simpleType> </xs:attribute> </xs:complexType> </xs:element></pre>																		

	<pre><xs:enumeration value="contentid"/> <xs:enumeration value="documentid"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="selectionelement" type="xs:string" use="required"/> <xs:attribute name="selectioncomparison" type="xs:string" use="required"/> <xs:attribute name="selectionvalue" type="xs:string" use="required"/> </xs:complexType> </xs:element></pre>
--	---

element **cmr_Selectionrule**

	The set of rules to be used to select a transient list of documents for authoring. A transient selection request returning a set of documents for authoring. The attribute 'SelectionType' specifies the type of selection rule to be applied that can be further qualified by the attribute SelectionElement and SelectionValue. Where 'SelectionType' as a value of 'Element' then an Inter-Publish Element must be specified in the attribute 'SelectionElement' with a value or set of values in the attribute 'SelectionValue'. More complex selection rules can be defined through static collections.
children	cmr_Selectionelement
used by	element cmr
notes	The set of rules to be used to select a transient list of documents for authoring.
xml	<pre> <xs:element name="cmr_Selectionrule"> <xs:notes> <xs:documentation>The set of rules to be used to select a transient list of documents for authoring.</xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Selectionelement" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **cmr_Status**

	cmr_Status A status report on all update and request actions. Return values are 'OK' or 'Failed' with a failure explanation in element 'description'.									
used by	elements auth cmr_Collectionlist cmr_Document cmr_Documentlist cmr_Documenttypelist cmr_Syndicationdocument cmr_Syndicationrequest cmr_Umplist cmr_Workflowlist									
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>status</td><td>xs:NMTOKEN</td><td>required</td></tr><tr><td>description</td><td>xs:string</td><td>optional</td></tr></table>	Name	Type	Use	status	xs:NMTOKEN	required	description	xs:string	optional
Name	Type	Use								
status	xs:NMTOKEN	required								
description	xs:string	optional								
notes	A status report on all update and request actions. Return values are 'OK' or 'Failed' with a failure explanation in element 'description'.									
xml	<pre><xs:element name="cmr_Status"> <xs:notes> <xs:documentation>A status report on all update and request actions. Return values are 'OK' or 'Failed' with a failure explanation in element 'description'.</xs:documentation> </xs:notes> <xs:complexType> <xs:attribute name="status" use="required"></pre>									

	<pre><xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="OK"/> <xs:enumeration value="Failed"/> </xs:restriction> </xs:simpleType> <xs:attribute> <xs:attribute name="description" type="xs:string" use="optional"/> </xs:complexType> </xs:element></pre>
--	--

element **cmr_Syndicationdocument**

	cmr_Syndicationdocument An XML encoded syndication document returned from a syndication request.						
type	extension of xs:string						
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>format</td><td>xs:NMTOKEN</td><td>required</td></tr></table>	Name	Type	Use	format	xs:NMTOKEN	required
Name	Type	Use					
format	xs:NMTOKEN	required					
notes	An XML encoded syndication document returned from a syndication request.						
xml	<pre><xs:element name="cmr_Syndicationdocument"> <xs:notes > <xs:documentation>An XML encoded syndication document returned from a syndication request.</xs:documentation> </xs:notes > <xs:complexType> <xs:simpleContent> <xs:extension base="xs:string"> <xs:attribute name="format" use="required"> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="rdf"/> <xs:enumeration value="rss"/> <xs:enumeration value="prism"/> <xs:enumeration value="newsml"/> </xs:restriction> </xs:simpleType> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>						

element **cmr_Syndicationdocument**

	cmr_Syndicationdocument cmr_Status 1..∞ A collection of syndication documents returned from a syndication request. A status report on all update and request actions. Return values are 'OK' or 'Failed' with a failure explanation in element 'description'.												
children	cmr_Status												
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>format</td><td>xs:string</td><td>required</td></tr><tr><td>requestid</td><td>xs:string</td><td>required</td></tr><tr><td>language</td><td>xs:string</td><td>required</td></tr></table>	Name	Type	Use	format	xs:string	required	requestid	xs:string	required	language	xs:string	required
Name	Type	Use											
format	xs:string	required											
requestid	xs:string	required											
language	xs:string	required											

notes	A collection of syndication documents returned from a syndication request.
xml	<pre> <xs:element name="cmr_Syndicationdocument"> <xs:notes> <xs:documentation>A collection of syndication documents returned from a syndication request.</xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Status" maxOccurs="unbounded"/> </xs:sequence> <xs:attribute name="format" type="xs:string" use="required"/> <xs:attribute name="requestid" type="xs:string" use="required"/> <xs:attribute name="language" type="xs:string" use="required"/> </xs:complexType> </xs:element> </pre>

element **cmr_Syndicationrequest**

	cmr_Syndicationrequest A syndication request document providing the syndication profile and requested format type. The syndication request may be based on a static or dynamic collection specified through a format request or a 'cmr_Urnlist' (which will return a fixed transformation format defined for this URL). Content name space and security are defined by the authorid supplied with the 'auth' xml. An optional attribute 'language' allows select of a language-specific result. cmr_Urnlist A list of requested presentation documents, fully transformed. Usually a URL list. cmr_Status 1..∞ A status report on all update and request actions. Return values are 'OK' or 'Failed' with a failure explanation in element 'description'.		
children	cmr_Urnlist cmr_Status		
used by	element	cmr_Syndicationrequestlist	
attributes	Name	Type	Use
	requestid	xs:string	
	language	xs:string	
	format	xs:NMTOKEN	required
notes	A syndication request document providing the syndication profile and requested format type. The syndication request may be based on a static or dynamic collection specified through a format request or a 'cmr_Urnlist' (which will return a fixed transformation format defined for this URL). Content name space and security are defined by the authorid supplied with the 'auth' xml. An optional attribute 'language' allows select of a language-specific result.		
xml	<pre> <xs:element name="cmr_Syndicationrequest"> <xs:notes> <xs:documentation>A syndication request document providing the syndication profile and requested format type. The syndication request may be based on a static or dynamic collection specified through a format request or a 'cmr_Urnlist' (which will return a fixed transformation format defined for this URL). Content name space and security are defined by the authorid supplied with the 'auth' xml. An optional attribute 'language' allows select of a language-specific result.</xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Urnlist"/> <xs:element ref="cmr_Status" maxOccurs="unbounded"/> </xs:sequence> <xs:attribute name="requestid" type="xs:string"/> </xs:complexType> </xs:element> </pre>		

	<pre><xs:attribute name="language" type="xs:string"/> <xs:attribute name="format" use="required"/> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="html"/> <xs:enumeration value="xhtml"/> <xs:enumeration value="rdf"/> <xs:enumeration value="rss"/> <xs:enumeration value="prism"/> <xs:enumeration value="newsml"/> </xs:restriction> </xs:simpleType> </xs:attribute> </xs:complexType> </xs:element></pre>
--	--

element **cmr_Syndicationrequestlist**

	cmr_Syndicationrequestlist A collection of syndication requests  cmr_Syndicationrequest A syndication request document providing the syndication profile and requested format type. The syndication request may be based on a static or dynamic collection specified through a format request or a 'cmr_Urnlist' (which will return a fixed transformation format defined for this URL). Content name space and security are defined by the authorid supplied with the 'auth' xml. An optional attribute 'language' allows select of a language-specific result.
children	cmr_Syndicationrequest
used by	element cmr
notes	A collection of syndication requests
xml	<pre><xs:element name="cmr_Syndicationrequestlist"> <xs:notes> <xs:documentation>A collection of syndication requests</xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Syndicationrequest"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **cmr_Transformation**

	cmr_Transformation A collection of transformation specifications - transformation type defines the transformation procedure.  cmr_Transformationtasklist A list of tasks to be performed to achieve a publishing process (the sequence is significant).
children	cmr_Transformationtasklist

used by	element	cmr_Document	
attributes	Name	Type	Use
	transformationtype	xs:string	required
	publishingtargetdomain	xs:string	required
	publishingtargetname	xs:string	required
	transformationlayout	xs:string	required
notes	A collection of transformation specifications - transformation type defines the transformation procedure - a value of empty or 'IPTL' allows the specification of an Inter-Publish transformation language task or task sequence defined by the specified transformation layout while 'script' defines a call to an external script defined by the elements specified by a transformation task list.		
xml	<pre> <xs:element name="cmr_Transformation"> <xs:notes> <xs:documentation>A collection of transformation specifications - transformation type defines the transformation procedure - a value of empty or 'IPTL' allows the specification of an Inter-Publish transformation language task or task sequence defined by the specified transformation layout while 'script' defines a call to an external script defined by the elements specified by a transformation task list. </xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Transformationtasklist" maxOccurs="unbounded"/> </xs:sequence> <xs:attribute name="transformationtype" type="xs:string" use="required"/> <xs:attribute name="publishingtargetdomain" type="xs:string" use="required"/> <xs:attribute name="publishingtargetname" type="xs:string" use="required"/> <xs:attribute name="transformationlayout" type="xs:string" use="required"/> </xs:complexType> </xs:element> </pre>		

element **cmr_Transformationtask**

	cmr_Transformationtask The input, output and transformation rules for a particular transformation task.															
used by	element cmr_Transformationtasklist															
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th></tr><tr><td>scripttype</td><td>xs:string</td><td>required</td></tr><tr><td>scriptserver</td><td>xs:string</td><td>required</td></tr><tr><td>scriptname</td><td>xs:string</td><td>required</td></tr><tr><td>scriptparameters</td><td>xs:string</td><td>required</td></tr></table>	Name	Type	Use	scripttype	xs:string	required	scriptserver	xs:string	required	scriptname	xs:string	required	scriptparameters	xs:string	required
Name	Type	Use														
scripttype	xs:string	required														
scriptserver	xs:string	required														
scriptname	xs:string	required														
scriptparameters	xs:string	required														
notes	A list of tasks to performed to achieve a publishing process (sequence is significant).															
xml	<pre><xs:element name="cmr_Transformationtask"> <xs:notes > <xs:documentation>A list of tasks to performed to achieve a publishing process (sequence is significant).</xs:documentation> </xs:notes > <xs:complexType> <xs:attribute name="scripttype" type="xs:string" use="required"/> <xs:attribute name="scriptserver" type="xs:string" use="required"/> <xs:attribute name="scriptname" type="xs:string" use="required"/> <xs:attribute name="scriptparameters" type="xs:string" use="required"/> </xs:complexType> </xs:element></pre>															


element **cmr_Transformationtasklist**

	cmr_Transformationtasklist cmr_Transformationtask A list of tasks to be performed to achieve a publishing process (the sequence is significant). The input, output and transformation rules for a particular transformation task.
children	cmr_Transformationtask
used by	elements cmr_Encodingvariant cmr_Transformation
notes	A list of tasks to performed to achieve a publishing process (the sequence is significant).
xml	<pre> <xs:element name="cmr_Transformationtasklist"> <xs:notes > <xs:documentation>A list of tasks to performed to achieve a publishing process (the sequence is significant).</xs:documentation> </xs:notes > <xs:complexType> <xs:sequence> <xs:element ref="cmr_Transformationtask" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>


element **cmr_url**

	cmr_url cmr_Encodeddocument The unique identification for a document requested, with an optional transformation specification and encoded documents. A single encoded and transformed document ready for final presentation.									
children	cmr_Encodeddocument									
used by	element cmr_Umlist									
attributes	<table><tr><td>Name</td><td>Type</td><td>Use</td></tr><tr><td>cmr_Transformation</td><td>xs:string</td><td>optional</td></tr><tr><td>requesttype</td><td>xs:NMTOKEN</td><td>required</td></tr></table>	Name	Type	Use	cmr_Transformation	xs:string	optional	requesttype	xs:NMTOKEN	required
Name	Type	Use								
cmr_Transformation	xs:string	optional								
requesttype	xs:NMTOKEN	required								
notes	The unique identification for a document requested, with an optional transformation specification and encoded documents.									
xml	<pre><xs:element name="cmr_url"> <xs:notes> <xs:documentation>The unique identification for a document requested, with an optional transformation specification and encoded documents.</xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Encodeddocument"/> </xs:sequence> <xs:attribute name="cmr_Transformation" type="xs:string" use="optional"/> <xs:attribute name="requesttype" use="required"/> </xs:complexType> </xs:element></pre>									

element **cmr_Urmlist**

	 cmr_Urmlist A list of requested presentation documents, fully transformed. Usually a URL list. cmr_url 1..∞ The unique identification for a document requested, with an optional transformation specification and encoded documents. cmr_Status 1..∞ A status report on all update and request actions. Return values are 'OK' or 'Failed' with a failure explanation in element 'description'.
children	cmr_url cmr_Status
used by	elements cmr cmr_Syndicationrequest
notes	A list of requested presentation documents, fully transformed. Usually a URL list.

element **cmr_Workflowlist**

	 cmr_Workflowlist A collection of workflow definitions which define any special actions to be taken when a document changes state (published, archived, unpublished, deleted). cmr_Workflow A workflow definition which defines any special actions to be taken when a document changes state (published, archived, unpublished, deleted). cmr_Status 1..∞ A status report on all update and request actions. Return values are 'OK' or 'Failed' with a failure explanation in element 'description'.
children	cmr_Workflow cmr_Status
used by	element cmr
notes	A collection of workflow definitions which define any special actions to be taken when a document changes state (published, archived, unpublished, deleted).
xml	<pre> <xs:element name="cmr_Workflowlist"> <xs:notes> <xs:documentation>A collection of workflow definitions which define any special actions to be taken when a document changes state (published, archived, unpublished, deleted).</xs:documentation> </xs:notes> <xs:complexType> <xs:sequence> <xs:element ref="cmr_Workflow"/> <xs:element ref="cmr_Status" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>